WATERWORKS

EASTON EAKM05

Easton Classic Two Hole Bridge Gooseneck Kitchen Faucet, Oak Lever Handles



TECHNICAL DETAILS

ADA Compliance: Yes

Adjustable versus Fixed Spray: Fixed Spray

Deck Thickness Maximum: 1 1/4"

Deck Thickness Minimum: 0"

Fittings Hole Diameter: 1"

Flow Restriction Options: 1.75, 1.5, 1.0

Handle Spread Maximum: 7 7/8"

Handle Spread Minimum: 7 7/8"

Handle Turn Angle: Quarter Turn

Index Color / Finish and Material: White Porcelain

Depth / Width: 13 1/4"

Height: 16"

Inlet Connection Size: 1/2"

Inlet Connection Type: Straight Male Threads

Inlet Supply Spread Maximum: 10 7/8"

Inlet Supply Spread Minimum: 4 7/8"

Length: 13 1/2"

Number of Holes: Two Hole

Primary Material: Brass

Restricted Maximum Flow Rate: 2.2 gpm

Spray Included in Unit: N

Suggested Application: Bar, Kitchen, Laundry

Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi

Water Pressure Recommended: 45.0 psi

L SHOWN IN EASTON CLASSIC TWO HOLE BRIDGE GOOSENECK KITCHEN FAUCET, OAK LEVER HANDLES| EAKMOS

INSPIRATION

Drawing on Edwardian style, Easton is the most extensive Waterworks family; a range of moods and a selection of products from fittings to furniture.

CODES & STANDARDS

Code # EAKM05: CEC

PRODUCT FEATURES

Brass metal is used for all trim and valve components

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing. Easton is our most comprehensive fittings family.

Easton has a clean-lined utilitarian profile, with a slightly elongated spout.

Standard flow rate is 2.2gpm (8.3 L/min) and State of California requires a maximum of 1.8gpm(6.8 L/min). Also available in other flow options. Contact a sales associate for details.

CERTIFICATIONS



PRODUCT (NOTES)

Spray sold separately

EASTON EAKM05

Easton Classic Two Hole Bridge Gooseneck Kitchen Faucet, Oak Lever Handles

