
HENRY

HNLS01

Henry Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles



TECHNICAL DETAILS

ADA Compliance: Yes Adjustable versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 1 5/8' Deck Thickness Minimum: 3/16" Drain Depth Maximum: 2 5/8" Drain Hole Diameter: 1 3/4" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 1/4" Handle Spread Maximum: 12" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Depth / Width: 7 5/8" Drain Depth Minimum: 3/8" Height: 3 5/8" Inlet Connection Size: 1/2" Inlet Connection Type: Male with Supply Nut Inlet Supply Spread Maximum: 12" Inlet Supply Spread Minimum: 8" Installation Type: Deck Mounted Integrated Diverter: N Integrated Spray: N Number of Handles: Two Number of Holes: Three Hole Primary Material: Brass Restricted Maximum Flow Rate: 1.2 gpm Spout Swivel: N Spray Included in Unit: N Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN HENRY LOW PROFILE THREE HOLE DECK MOUNTED LAVATORY FAUCET WITH METAL CROSS HANDLES HNLS01

INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

CODES & STANDARDS

Code # HNLS01X: Complies with ASME A112.18.1/CSA B125.1, ASME A112.18.2 / CSA B125.2, NSF, CEC 61, ADA and 0.25% Weighted Average Lead Content. Certified with IAPMO, cUPC, NSF, CEC and State of MA.

PRODUCT FEATURES

Metal cross handles Includes European size push touch drain The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing. Stocked in Chrome, Nickel, Matte Nickel, and Unlacquered Brass Available in 1.2gpm (4.5L/min) flow rate

CERTIFICATIONS



HENRY

HNLS01

Henry Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles

