WATERWORKS

HNTF01 **HENRY**

Henry Low Profile Concealed Tub Filler With Handshower and Metal Cross Handles



SHOWN IN HENRY LOW PROFILE CONCEALED TUB FILLER WITH HANDSHOWER AND METAL CROSS HANDLES| HNTF01

TECHNICAL DETAILS

ADA Compliance: Yes Adjustable versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 1 3/8" Deck Thickness Minimum: 3/16" Diameter of Head: 1 7/8" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 5/8" Flow Restriction Options: 2.0, 1.75, 1.5, 0.92 Handle Spread Maximum: 12" Handle Spread Minimum: 10" Handle Turn Angle: Quarter Turn Handshower / Spray Hose Length: 79" Depth / Width: 10" Height: 6 5/16" Inlet Connection Size: 3/4" Inlet Connection Type: Male NPT Adapter Inlet Supply Spread Maximum: 12" Inlet Supply Spread Minimum: 10" Installation Type: Deck Mounted Integrated Diverter: N Integrated Spray: N Length: 17 3/8" Number of Handles: Two Number of Holes: Four Hole Primary Material: Brass Restricted Maximum Flow Rate: 2.5 gpm Spout Swivel: N Spray Included in Unit: N Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi

INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

CODES & STANDARDS

Water Pressure Recommended: 45.0 psi

Code # HNTU01X: Complies with ASME A112.18.1/CSA B125.1, ASTM E 1621-05 & ANSI A117.1 ADA. Certified with IAPMO, cUPC & State of MA

PRODUCT FEATURES

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing. Brass material is used for components

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min). State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details.









HENRY HNTF01

Henry Low Profile Concealed Tub Filler With Handshower and Metal Cross Handles

