WATERWORKS

HENRY HNXT60

Henry Exposed Floor Mounted Tub Filler With Handshower and Metal Cross Handles



L SHOWN IN HENRY EXPOSED FLOOR MOUNTED TUB FILLER WITH HANDSHOWER AND METAL CROSS HANDLES| HNXT60

TECHNICAL DETAILS

ADA Compliance: Yes

Adjustable versus Fixed Spray: Fixed Spray

Diameter of Head: 1 7/8"

Diameter of Legs / Tubes: 1 9/16"

Escutcheon Primary Material: Brass

Fittings Hole Diameter: 1 1/8"

Flow Restriction Options: 2.5, 2.0, 1.75, 1.5, 0.92

Handle Spread Maximum: 8"

Handle Spread Minimum: 8"

Handle Turn Angle: Quarter Turn

Handshower / Spray Hose Length: 59"

Depth / Width: 10 13/16"

Height: 41 1/16"

Inlet Connection Size: 3/4"

Inlet Connection Type: Copper Sweat

Inlet Supply Spread Maximum: 8"

Inlet Supply Spread Minimum: 8"

Installation Type: Freestanding

Integrated Diverter: N Integrated Spray: N

Number of Handles: Two

Number of Holes: Two Hole

Pivot: N

Primary Material: Brass

Spout Swivel: N

Spray Included in Unit: N Suggested Application: Bath

Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi

Water Pressure Minimum: 20.0 psi

Water Pressure Recommended: 45.0 psi

INSPIRATION

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

CODES & STANDARDS

Code # HNTU60: Complies with ASME A112.18.1/CSA B125.1, CEC, ADA and 0.25% Weighted Average Lead Content. Certified with IAPMO, cUPC, NSF, CEC, DOE, State of MA and WRAS.

PRODUCT FEATURES

The manufacturing process encompasses casting, turning, forging, hand-fitting and hand polishing. Brass material is used for components.

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min) for Handshower. State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details









HENRY HNXT60

Henry Exposed Floor Mounted Tub Filler With Handshower and Metal Cross Handles

