WATERWORKS

R.W. ATLAS RWXS41

R.W. Atlas Exposed Thermostatic System with 8" Shower Rose, Arm, Handshower, Metal Wheel and Lever Handles



TECHNICAL DETAILS

ADA Compliance: No
Adjustable versus Fixed Spray: Fixed Spray
Diameter of Head: 8 9/16"
Diameter of Legs / Tubes: 1 1/8"
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 1"
Flow Restriction Options: 2.5, 2.2, 2.0, 1.75, 1.5, 0.92
Handshower / Spray Hose Length: 59"
Depth / Width: 29 3/8"
Height: 79 1/8"
Inlet Connection Size: 3/4"

Inlet Connection Type: Copper Compression Inlet Supply Spread Maximum: 11 3/4" Inlet Supply Spread Minimum: 11 1/2" Installation Type: Wall Mounted Integrated Diverter: N Length: 14" Number of Handles: Three

Pivot: Y Primary Material: Brass Spray Included in Unit: N Suggested Application: Bath Valve Material: Bi-metal Strip Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

L SHOWN IN R.W. ATLAS EXPOSED THERMOSTATIC SYSTEM WITH 8" SHOWER ROSE, ARM, HANDSHOWER, METAL WHEEL

INSPIRATION

Powerful shapes, genuine materials and unique aesthetic details. The original, impeccable vision of R.W. Atlas pairs American ingenuity with European craftsmanship.

CODES & STANDARDS

Code # RWXS40: Complies with ASME A112.18.1/CSA B125.1, ADA and 0.25% Weighted Average Lead Content. Certified with IAPMO, cUPC, and State of MA.

PRODUCT FEATURES

Built in Anti-scald protection.

Stocked in 2.5gpm (9.5 L/min) and 1.75gpm (6.6 L/min). State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details.









R.W. ATLAS RWXS41

R.W. Atlas Exposed Thermostatic System with 8" Shower Rose, Arm, Handshower, Metal Wheel and Lever Handles

