## WATERWORKS

HNXS60 **HENRY** 

Henry Exposed Thermostatic Shower System with 8" Shower Head, Handshower, Metal Cross Diverter Handle, Metal Lever and Cross



SHOWN IN HENRY EXPOSED THERMOSTATIC SHOWER SYSTEM WITH 8" SHOWER HEAD, HANDSHOWER, METAL CROSS

## **INSPIRATION**

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

## PRODUCT FEATURES

Available Late Spring 2018

Features an intergrated thermostatic shut-off valve

Stocked in Nickel, Chrome, Unlacquered Brass, and Matte Nickel finishes

Standard flow rate is 2.5gpm (9.5 L/min). Also available in high efficient flow options. Contact your sales associate or call 1 (800) 899-6757 for details.

## **TECHNICAL DETAILS**

Adjustable versus Fixed Spray: Fixed Spray

Diameter of Head: 7 3/4" Diameter of Legs / Tubes: 1 1/8" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 1/8"

Flow Restriction Options: Shower Head: 2.5, 2.0, 1.75, 1.5 and

Handshower: 2.5, 2.2, 2.0, 1.75, 1.5, 1.2, 0.92 Handle Spread Maximum: 5 11/16" Handle Spread Minimum: 5 11/16" Handle Turn Angle: Quarter Turn Handshower / Spray Hose Length: 59"

Inlet Connection Size: 3/4"

Inlet Connection Type: Copper Compression Inlet Supply Spread Maximum: 11 5/8" Inlet Supply Spread Minimum: 11 1/8" Installation Type: Wall Mounted Integrated Diverter: Y Integrated Spray: N Number of Handles: Three

Number of Holes: Two Hole Pivot: Y

Primary Material: Brass Spray Included in Unit: Y Suggested Application: Bath Valve Material: Wax Element Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi









HENRY HNXS60

Henry Exposed Thermostatic Shower System with 8" Shower Head, Handshower, Metal Cross Diverter Handle, Metal Lever and Cross

