## HENRY

# HNXS70

Henry Exposed Thermostatic Shower System with 8" Shower Head, Handshower, Metal Lever Diverter Handle, Metal Lever and Cross



#### TECHNICAL DETAILS

Adjustable versus Fixed Spray: Fixed Spray Diameter of Head: 7 3/4" Diameter of Legs / Tubes: 1 1/8" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 1/8" Flow Restriction Options: Shower Head: 2.5, 2.0, 1.75, 1.5 and Handshower: 2.5, 2.2, 2.0, 1.75, 1.5, 1.2, 0.92 Handle Spread Maximum: 5 11/16" Handle Spread Minimum: 5 11/16" Handle Turn Angle: Quarter Turn Handshower / Spray Hose Length: 59" Inlet Connection Size: 3/4" Inlet Connection Type: Copper Compression Inlet Supply Spread Maximum: 11 5/8" Inlet Supply Spread Minimum: 11 1/8" Installation Type: Wall Mounted Integrated Diverter: Y Integrated Spray: N Number of Handles: Three Number of Holes: Two Hole Pivot: Y Primary Material: Brass Spray Included in Unit: Y Suggested Application: Bath Valve Material: Wax Element Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

L SHOWN IN HENRY EXPOSED THERMOSTATIC SHOWER SYSTEM WITH 8" SHOWER HEAD, HANDSHOWER, METAL LEVER

#### **INSPIRATION**

Influenced by the connection of industry and art Henry easily transitions between modern, traditional, utilitarian and classic settings.

#### **PRODUCT FEATURES**

Available Late Spring 2018 Features an intergrated thermostatic shut-off valve Stocked in Nickel, Chrome, Unlacquered Brass, and Matte Nickel finishes Standard flow rate is 2.5gpm (9.5 L/min). Also available in high efficient flow options. Contact your sales associate or call 1 (800) 899-6757 for details.





# HENRY

## HNXS70

Henry Exposed Thermostatic Shower System with 8" Shower Head, Handshower, Metal Lever Diverter Handle, Metal Lever and Cross

