

Luminaire




Application Notes

* Various stones are suitable for use in wet environments, including steam showers, if properly installed,sealed, and maintained. Please inquire.

⁺ Some stones are suitable in tropical/subtropical climates. Testing may be required. Please inquire.

Installation / Maintenance • WATERWORKS ASSUMES NO RESPONSIBILITY FOR INSTALLATION

- Installation constitutes acceptance.
- Mosaic should be installed by a licensed and experienced tile setter.
- Refer to TCNA (Tile Council of North America) or ANSI standards for installation guidelines.
- All mosaics must be inspected PRIOR to installation.
- Dry lay mosaics prior to installation to allow for blending of color variation.
- Stone must be sealed before grout installation to allow grout to release and prevent staining.
- Stone and grout should be sealed after installation and maintained regularly.



SAMPLING IS RECOMMENDED TO UNDERSTAND VARIATION OF MATERIAL


Product Variation

Color and surface variation is an inherent characteristic of natural materials and should be expected. Thickness and grout width will also vary and should be expected. Refer to our color variation ranking for further details. Please inquire for additional information.

Custom Opportunities Available

Minimums and extended lead-times may apply.

Please contact your local Waterworks showroom or our direct sales team at 800.899.6757.



Suggested Grout Lines

Varies- Please follow mosaic sheet