ISLA ISS200

Isla 10" Rain Showerhead with 6" Ceiling Mounted Shower



TECHNICAL DETAILS

Adjustable Versus Fixed Spray: Fixed Fittings Hole Diameter: 1 1/4" Inlet Connection Size: 1/2" Inlet Connection Type: Male NPT

Pivot: Y

Primary Material: Brass

Restricted Maximum Flow Rate: 1.75 gpm Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN ISLA 10" RAIN SHOWERHEAD WITH 6" CEILING MOUNTED SHOWER ARM | ISS200

INSPIRATION CODES & STANDARDS

Pure, timeless, unique and versatile - sculptural organic forms meet advanced engineering in this inspiring collection of fittings, hardware and accessories.

PRODUCT FEATURES

Made of Brass

Features a swivel 10" rain showerhead with easy clean rubber nozzles

Includes a 6" ceiling mounted shower arm

Stocked in Brass, Chrome and Nickel

Rain showerhead available in 1.75gpm (6.6L/min) flow rate


CERTIFICATIONS

PRODUCT (NOTES)

ISLA ISS200


SCALE: 3"=1'-0"


Isla 10" Rain Showerhead with 6" Ceiling Mounted Shower Arm



STYLE NO.	DIM "A"	DIM "B"
FLS200	10 ⁵ / ₁₆ " [261mm]	6 ⁹ / ₁₆ " [167mm]
ISS200		
FLS201	16 ⁵ / ₁₆ " [414mm]	12 ⁹ / ₁₆ " [319mm]
ISS201		
FLS202	22 ⁵ / ₁₆ " [566mm]	18 ⁹ / ₁₆ " [472mm]
ISS202		

CEILING VIEW





PRODUCT SUPPORT 800.927.2120 OPT 2 | WATERWORKS.COM