


OPUS

OPS102

Opus 10" Rain Showerhead with 18" Ceiling Mounted Shower Arm



SHOWN IN OPUS 10" RAIN SHOWERHEAD WITH 18" CEILING MOUNTED SHOWER ARM | OPS102

TECHNICAL DETAILS

Adjustable Versus Fixed Spray: Fixed
Fittings Hole Diameter: 1 1/4"
Inlet Connection Size: 1/2"
Inlet Connection Type: Male NPT
Pivot: Y
Primary Material: Brass
Restricted Maximum Flow Rate: 1.75 gpm
Water Pressure Maximum: 85.0 psi
Water Pressure Minimum: 20.0 psi
Water Pressure Recommended: 45.0 psi

INSPIRATION

Opus incorporates a range of sophisticated aesthetic notes, with graceful curves that create a jewel-like refinement.

CODES & STANDARDS

PRODUCT FEATURES

Made of Brass

Features a swivel 10" rain showerhead with easy clean rubber nozzles

Includes an 18" ceiling mounted shower arm

Stocked in Brass, Chrome and Nickel

Rain showerhead available in 1.75gpm (6.6L/min) flow rate


CERTIFICATIONS

PRODUCT (NOTES)

OPUS


OPS102

Opus 10" Rain Showerhead with 18" Ceiling Mounted Shower Arm




CEILING VIEW SCALE: 1/2"=1'-0"

STYLE NO.	DIM "A"	DIM "B"
EAS100	11 1/8" [283mm]	6 9/16" [167mm]
OPS100		
EAS101	17 1/8" [435mm]	12 9/16" [319mm]
OPS101		
EAS102	23 1/8" [588mm]	18 9/16" [472mm]
OPS102		



FRONT VIEW SCALE: 1/2"=1'-0"



SIDE VIEW SCALE: 1/2"=1'-0"