
HIGHGATE

Exposed Wall Mounted Tub Filler With Handshower

Metal Cross Handles **Style No.** HGXT20



SPECIFICATIONS:

Handle Spread: 7-5/8" (NOT ADJUSTABLE)

Inlet Connection Size: 3/4"
Inlet Connection Type: Male NPT

Inlet Connection Spread 7-5/8" (NOT ADJUSTABLE)

Maximum Water Pressure: 80psi Minimum Water Pressure: 20psi Fittings Hole Diameter: 1-1/4"

Recommended Water Pressure: 45psi

Spout Reach: 8-7/8"

IMPORTANT:

- To ensure this product is installed properly, you must read and follow these guidelines.
- > The owner/user of this product must keep this information for future reference.
- Be sure your installation conforms to federal state, and local codes. Anti-scald protection is the responsibility of the installer and according to applicable codes.
- In the State of Massachusetts, all installations must comply with the rules and regulations set forth within 248 CMR.
- > This product must be installed by a professional licensed contractor.
- Product should be on-site prior to rough-in. This allows the installer to visualize the installation and verify the inlet connection spread.
- Refer to the specifications and assembly drawings attached. Product is sold partially assembled but

INSTALLATION GUIDELINES

shown fully disassembled for illustrative and service purposes only.

- > Check tub measurements to assure the spout projects far enough into the tub.
- > Inspect this product to ensure you have all the parts required for proper installation.
- > Use only a strap wrench or protected/smooth-jaw wrench on any finished surface.
- ➤ Run 3/4" supply lines for maximum flow.
- Install accessible hot and cold service stop valves to facilitate servicing.

ROUGH-IN:

- 1. Run well supported 3/4" hot and cold supply lines for maximum water flow.
- 2. Install 3/4" Female NPT adapters (NOT SUPPLIED). Ensure that the adapters are secure, level, at the proper spread of 7-5/8" (NOT ADJUSTABLE) and at equal depths. The final distance the nipples (1) must project from the surface of the finished wall must be between 1-1/8" and 2-1/4". See Figure-01.

TUB FILLER INSTALLATION:

IMPORTANT:

- > Verify the 7-5/8" inlet supply spread prior to installation.
- 3. Thread the 3/4" NPT end of the nipples (1) to the 3/4" Female NPT adapters (NOT SUPPLIED).
- 4. Slide the escutcheons (3) over the nipples and up to the finished wall. Make sure the washer (2) is behind each escutcheon.

Figure - 01

Finished Wall

1/8" MIN
2/4" MAX

PROJECTION FROM
FINISHED WALL

75/8"

75/8"

NPT Nipple

These guidelines have been prepared for the professional contractor to aid in the installation of: HIGHGATE WALL MOUNTED TUB FILLER WITH HANDSHOWER & METAL CROSS HANDLES (STYLE# HGXT20)

(STITE:# FIGAT2D)
All dimensions are based on original specification and are subject to change and variation. Please consult your Design Associate for current specifications.

WATERWORKS

6.11.2012 Page 1 of 3

HIGHGATE

Exposed Wall Mounted Tub Filler With Handshower

INSTALLATION GUIDELINES

5. Hold the valve body (5) up to the nipples and attach it by threading the valve body's union nuts onto the nipples. Ensure that the washer (4) is in each nut.

HANDSHOWER INSTALLATION:

- 6. Attach the handshower cradle (8) to the valve body (5) and ensure that washer (4) is located in the cradle inlet. NOTE: A check valve is located at the inlet of the cradle and a flow regulating check valve is located at the outlet of the cradle.
- 7. Connect one end of the handshower hose (7) to the handshower (6).
- 8. Connect the other end of the handshower hose (7) to the handshower cradle outlet (8). Place the handshower on the cradle.

INSPECT THE INSTALLATION:

- 9. Turn on the supplies then open the hot and cold valves to flush out any debris in the supply lines before diverting to the handshower. To divert to the handshower turn the diverter lever handle, which is the center handle.
- 10. Carefully inspect all connections for leaks and check for proper operation.
- If further assistance is required, please contact Product Support at 1-800-927-2120 (9am-6pm EST).

These guidelines have been prepared for the professional contractor to aid in the installation of: HIGHGATE WALL MOUNTED TUB FILLER WITH HANDSHOWER & METAL CROSS HANDLES (STYLE# HGXT20)


All dimensions are based on original specification and are subject to change and variation. Please consult your Design Associate for current specifications.

WATERWORKS

HIGHGATE

Exposed Wall Mounted Tub Filler With Handshower

INSTALLATION GUIDELINES



	Description	QTY
1	Nipple	2
2	Foam Washer	2
3	Escutcheon	2
4	Rubber Washer	3
5	Valve Body	1
6	Handshower	1
7	Handshower Hose	1
8	Cradle	1


These guidelines have been prepared for the professional contractor to aid in the installation of: HIGHGATE WALL MOUNTED TUB FILLER WITH HANDSHOWER & METAL CROSS HANDLES (STYLE# HGXT20)


All dimensions are based on original specification and are subject to change and variation. Please consult your Design Associate for current specifications.

WATERWORKS STUDIO

WATERWORKS STUDIO

SERVICE PARTS





WELCOME TO

WATERWORKS STUDIO

Everything you need, nothing more.

Over thirty years of experience distilled into signature fittings, surfaces, textiles, and accessories. Waterworks Studio is an edited collection of design solutions curated to be concise, engineered to be complete, and crafted for quality.

TO ORDER PARTS CALL 1 (800) 927-2120 (EXT 2)

Order by part number and specify color, finish, or other options if required.

Product Support

Our Product Support team provides troubleshooting and technical problem resolution, including replacement parts and installation recommendations throughout the life of your product.


Product Support is available Monday through Friday 8AM to 6PM EST.

LIMITED LIFETIME WARRANTY

Our warranty covers repair and replacement of Waterworks products if within the applicable coverage period and deemed defective by Waterworks. Waterworks will, at its option, repair or replace such products; this does not include installation costs, labor charges, or other incidental or consequential costs.

To obtain your complete warranty or inquire about warranty service, please visit us at www.waterworks. com or contact our Product Support Team.

MAIN KITS




STYLES: HGXT20, HGXT40


*FINISH/COLOR MUST BE SPECIFIED WHEN ORDERING ++SUPPLIED AS A PAIR

KIT COMPONENTS





KIT COMPONENTS



WATERWORKS

STYLES: HGXT20, HGXT40


*FINISH/COLOR MUST BE SPECIFIED WHEN ORDERING ++SUPPLIED AS A PAIR


KIT COMPONENTS



KIT COMPONENTS








STYLES: HGXT20, HGXT40


*FINISH/COLOR MUST BE SPECIFIED WHEN ORDERING ++SUPPLIED AS A PAIR

KIT COMPONENTS



KIT COMPONENTS





WATERWORKS STUDIO


STYLES: HGXT20, HGXT40


*FINISH/COLOR MUST BE SPECIFIED WHEN ORDERING ++SUPPLIED AS A PAIR

KIT COMPONENTS









SERVICE PARTS INDEX

STYLE	DESCRIPTION	<u>PG</u>
103599*	DIVERTER HANDLE KIT	10
956299	DIVERTER KIT	7
337847	COUNTERCLOCKWISE ON VALVE CARTRIDGE	2
103606*	CROSS HANDLE KIT WITH COLD INDICE	3
103598*	CROSS HANDLE KIT WITH HOT INDICE	2
723681*	HANDSHOWER CRADLE KIT	8
781448*	HANDSHOWER HOSE KIT	3
194193*	SPOUT KIT	6
009377*	SPRAY KIT	9
103597*	UNION KIT	4
103600*	UNION KIT	5

DOCUMENT: SPHG09_REV01



PRODUCT SUPPORT

60 BACKUS AVENUE
DANBURY, CT 06810
1 (800) 927-2120 (EXT 2)
WWW.WATERWORKS.COM/STUDIO