

FLYTE

FLLS50

Flyte Low Profile One Hole Deck Mounted Lavatory Faucet with Metal Lever Handles



SHOWN IN FLYTE LOW PROFILE ONE HOLE DECK MOUNTED LAVATORY FAUCET WITH METAL LEVER HANDLES | FLLS50

TECHNICAL DETAILS

ADA Compliance: Yes
 Adjustable Versus Fixed Spray: Fixed Spray
 Deck Thickness Maximum: 3 13/16"
 Deck Thickness Minimum: 0"
 Depth/Width: 7 5/8"
 Drain Depth Maximum: 2"
 Drain Depth Minimum: 1 1/4"
 Drain Hole Diameter: 1 1/2"
 Escutcheon Primary Material: Brass
 Fittings Hole Diameter: 1 3/8"
 Flow Restriction Options: 1.2
 Handle Turn Angle: Half Turn
 Height: 5 7/8"
 Inlet Connection Size: 3/8"
 Inlet Connection Type: Compression Connector Hoses
 Installation Type: Deck Mounted
 Integrated Diverter: N
 Integrated Spray: N
 Length: 15 1/4"
 Number Of Handles: One
 Number Of Holes: One Hole
 Primary Material: Brass
 Restricted Maximum Flow Rate: 1.2 gpm
 Spout Swivel: N
 Spray Included In Unit: N
 Suggested Application: Bath
 Valve Material: Ceramic
 Water Pressure Maximum: 85.0 psi
 Water Pressure Minimum: 20.0 psi
 Water Pressure Recommended: 45.0 psi

INSPIRATION

Pure Modernism. Like minimalist works of art, the elegant proportions of these light, fluid elements bring sculptural reference to a room.

CODES & STANDARDS

FLLS50X, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1, CEC, State of MA

PRODUCT FEATURES

Push touch USA style drain included.

This item is stocked in a Chrome and Nickel finishes.

Lever Handle

Available in 1.2gpm (4.5L/min) flow rate

CERTIFICATIONS



PRODUCT (NOTES)

FLYTE

FLLS50

Flyte Low Profile One Hole Deck Mounted Lavatory Faucet with Metal Lever Handles

