FLYTE FLLS01

Flyte Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles



SHOWN IN FLYTE LOW PROFILE THREE HOLE DECK MOUNTED LAVATORY FAUCET WITH METAL CROSS HANDLES | FLLS01

TECHNICAL DETAILS

ADA Compliance: Yes

Adjustable Versus Fixed Spray: Fixed Spray Deck Thickness Maximum: 2 1/2"

Deck Thickness Minimum: 3/8" Depth/Width: 7 5/8" Drain Depth Maximum: 2" Drain Depth Minimum: 1 1/4" Drain Hole Diameter: 1 1/2" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 3/8" Flow Restriction Options: 1.2

Handle Spread Maximum: 12" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn

Height: 4 1/8"

Inlet Connection Size: 1/2"

Inlet Connection Type: Male with Supply Nut

Inlet Supply Spread Maximum: 12" Inlet Supply Spread Minimum: 8" Installation Type: Deck Mounted

Integrated Diverter: N Integrated Spray: N Length: 15 1/4"

Number Of Handles: Two Number Of Holes: Three Hole Primary Material: Brass

Restricted Maximum Flow Rate: 1.2 gpm

Spout Swivel: N

Spray Included In Unit: N Suggested Application: Bath Valve Material: Ceramic

Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

INSPIRATION

Pure Modernism. Like minimalist works of art, the elegant proportions of these light, fluid elements bring sculptural reference to a room.

CODES & STANDARDS

FLLS01X, NSF/ANSI/CAN 61:Q < 1, NSF/ANSI/CAN 372, ASME A112.18.1/CSA B125.1, CEC, State of MA

PRODUCT FEATURES

Push touch USA style drain included.

This item is stocked in a Chrome and Nickel finishes.

Cross Handles

Available in 1.2gpm (4.5L/min) flow rate

CERTIFICATIONS





PRODUCT (NOTES)

FLYTE FLLS01

Flyte Low Profile Three Hole Deck Mounted Lavatory Faucet with Metal Cross Handles

