# WATERWORKS

LUDLOW LDXT60

Ludlow Floor Mounted Exposed Tub Filler with Handshower and Metal Cross Handles



SHOWN IN LUDLOW FLOOR MOUNTED EXPOSED TUB FILLER WITH HANDSHOWER AND METAL CROSS HANDLES| LDXT60

#### **TECHNICAL DETAILS**

Adjustable versus Fixed Spray: Fixed Spray Diameter of Head: 2 1/16" Diameter of Legs / Tubes: 1 7/16" Escutcheon Primary Material: Brass Fittings Hole Diameter: 1 1/4" Flow Restriction Options: 2.0, 1.75, 1.5, 0.92 Handle Spread Maximum: 8" Handle Spread Minimum: 8" Handle Turn Angle: Quarter Turn Handshower / Spray Hose Length: 68" Depth / Width: 10 7/8" Height: 38 1/8" Inlet Connection Size: 3/4" Inlet Connection Type: Copper Sweat Inlet Supply Spread Maximum: 8" Inlet Supply Spread Minimum: 8" Installation Type: Freestanding Integrated Diverter: N Integrated Spray: N Length: 14 1/2" Number of Handles: Two Number of Holes: Two Hole Pivot: N Primary Material: Brass Spout Swivel: N Spray Included in Unit: N Suggested Application: Bath Valve Material: Ceramic Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

#### **INSPIRATION**

A touch of classic Americana. Our fresh take on iconic industrial design has clean lines and dimensional details, including exposed screws and square plates.

## **CODES & STANDARDS**

Code # LDXT60Y: Certified with cUPC, NSF, IAPMO, CSA

### PRODUCT FEATURES

Handshower is easy and comfortable to grip.

This item is stocked in a Chrome, Nickel and Unlacquered Brass finishes.

Diverter button allows bather to move water from spout to handshower

Stocked in 2.5gpm (7.6 L/min) and 1.75gpm (6.6 L/min) for Handshower. State of California requires 1.75gpm (6.6 L/min) to comply with their water conservation requirements. Other flow options are available to order, contact your sales associate or call 1 (800) 899-6757 for details









LUDLOW LDXT60

Ludlow Floor Mounted Exposed Tub Filler with Handshower and Metal Cross Handles

