HIGHGATE HGLS60

Highgate Low Profile Three Hole Wall Mounted Lavatory Faucet with Metal Cross Handles and Valve



## **TECHNICAL DETAILS**

ADA Compliance: Yes
Control Valve Rough-in Depth Maximum: 4 3/8"
Control Valve Rough-in Depth Minimum: 1 7/8"
Drain Assembly Materials: Brass
Drain Depth Maximum: 2"
Drain Style: USA Lift & Turn
Escutcheon Primary Material: Brass
Fittings Hole Diameter: 1 3/8"

Flow Restriction Options: 1.0 , 1.2 , 1.5 , 1.75 , 2.2 Handle Spread Maximum: 8" Handle Spread Minimum: 8"

Handle Turn Angle: Quarter Turn Drain Depth Minimum: 1 1/2"

Height: 3" Inlet Connection Size: 1/2" Inlet Connection Type: Female NPT

Inlet Connection Type: Female NPT Inlet Supply Spread Maximum: 8" Inlet Supply Spread Minimum: 8" Length: 10 3/8"

Number of Holes: Three Hole Primary Material: Brass Restricted Maximum Flow Rate: 1.2 gpm

Valve Material: Brass, Ceramic Water Pressure Maximum: 80.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

L Shown in Highgate Low Profile three hole wall mounted Lavatory Faucet with metal cross handles and

## **INSPIRATION**

Our take on old English style: simple, functional shapes, detailed with white porcelain indices and hexagonal accents for a timeless feel.

## **CODES & STANDARDS**

Code # HGLS60: CEC

## **PRODUCT FEATURES**

Low profile faucet with stepped handle bases, cast of brass

This item is stocked in Chrome, Nickel and Unlacquered Brass finishes

Cross handles feature hot and cold markings on white porcelain indices  $% \left( 1\right) =\left( 1\right) \left( 1\right) \left($ 

Standard flow rate is 1.2gpm (4.5 L/min) and meets State of California requirements. Also available in other flow options. Contact a sales associate for details.

HIGHGATE HGLS60

Highgate Low Profile Three Hole Wall Mounted Lavatory Faucet with Metal Cross Handles and Valve

