FLYTE FLS202

Flyte 10" Rain Showerhead with 18" Ceiling Mounted Shower



## **TECHNICAL DETAILS**

Adjustable Versus Fixed Spray: Fixed Fittings Hole Diameter: 1 1/4" Inlet Connection Size: 1/2" Inlet Connection Type: Male NPT Pivot: Y

Primary Material: Brass

Restricted Maximum Flow Rate: 1.75 gpm Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN FLYTE 10" RAIN SHOWERHEAD WITH 18" CEILING MOUNTED SHOWER ARM | FLS202

INSPIRATION

Pure Modernism. Like minimalist works of art, the elegant proportions of these light, fluid elements bring sculptural reference to a room.

**CODES & STANDARDS** 

**PRODUCT FEATURES** 

Made of Brass

Features a swivel 10" rain showerhead with easy clean rubber nozzles

Includes an 18" ceiling mounted shower arm

Stocked in Brass, Chrome and Nickel

Rain showerhead available in 1.75gpm (6.6L/min) flow rate


**CERTIFICATIONS** 

PRODUCT (NOTES)

FLYTE FLS202


SCALE: 3"=1'-0"


Flyte 10" Rain Showerhead with 18" Ceiling Mounted Shower



STYLE NO.	DIM "A"	DIM "B"
FLS200	10 <sup>5</sup> / <sub>16</sub> " [261mm]	6 <sup>9</sup> / <sub>16</sub> " [167mm]
ISS200		
FLS201	16 <sup>5</sup> ⁄ <sub>16</sub> " [414mm]	12 <sup>9</sup> / <sub>16</sub> " [319mm]
ISS201		
FLS202	22 <sup>5</sup> / <sub>16</sub> " [566mm]	18 <sup>9</sup> / <sub>16</sub> " [472mm]
ISS202		

CEILING VIEW





PRODUCT SUPPORT 800.927.2120 OPT 2 | WATERWORKS.COM