FLYTE FLS221

Flyte 12" Rain Showerhead with 12" Ceiling Mounted Shower Arm



TECHNICAL DETAILS

Adjustable Versus Fixed Spray: Fixed Fittings Hole Diameter: 1 1/4" Inlet Connection Size: 1/2" Inlet Connection Type: Male NPT Pivot: Y

Primary Material: Brass

Restricted Maximum Flow Rate: 1.75 gpm Water Pressure Maximum: 85.0 psi Water Pressure Minimum: 20.0 psi Water Pressure Recommended: 45.0 psi

SHOWN IN FLYTE 12" RAIN SHOWERHEAD WITH 12" CEILING MOUNTED SHOWER ARM | FLS221

INSPIRATION

Pure Modernism. Like minimalist works of art, the elegant proportions of these light, fluid elements bring sculptural reference to a room.

CODES & STANDARDS

PRODUCT FEATURES

Made of Brass

Features a swivel 12" rain showerhead with easy clean rubber nozzles

Includes a 12" ceiling mounted shower arm

Stocked in Brass, Chrome and Nickel

Rain showerhead available in 1.75gpm (6.6L/min) flow rate

CERTIFICATIONS

PRODUCT (NOTES)

FLYTE FLS221

Flyte 12" Rain Showerhead with 12" Ceiling Mounted Shower Arm

